

Aspire 5720 Series Specifications

Part Number: Aspire5720 Aspire 5720

Feature	Description
Part Number	Varies by specifications
Processor / Speed	Intel® Centrino® Duo mobile processor technology, featuring: Intel® Core™2 Duo mobile processor T7300/T7500/T7700 (4 MB L2 cache, 2/2.2/2.4 GHz, 800 MHz FSB), or T7100 (2 MB L2 cache, 1.8 GHz, 800 MHz), supporting Intel® 64 architecture
Core Logic Chipset	Mobile Intel® GM965 Express
System Bus Speed	800 MHz
RAM / Max RAM	Up to 2 GB of DDR2 667 MHz memory, upgradeable to 4 GB using two soDIMM modules (dual-channel support)
Video Subsystem	Mobile Intel® GM965 Express Chipset with integrated 3D graphics, featuring Intel® Graphics Media Accelerator (GMA) X3100 with up to 358 MB of Intel® Dynamic Video Memory Technology 4.0 (8 MB of dedicated system memory, up to 358 MB of shared system memory), supporting Microsoft® DirectX® 9 and DirectX® 10
LCD Properties	15.4" WXGA high-brightness TFT LCD, 1280 x 800 pixel resolution
Hard Disk Drive	up to 160 GB with enhanced Acer DASP (Disk Anti-Shock Protection)
Optical Drive	8X DVD-Super Multi or DVD/CD-RW Combo (varies by model)
Battery, Primary	ACPI 3.0 CPU power management standard: supports Standby and Hibernation power-saving modes with up to 3-hour battery life with 44.4 W 4000 mAh 6-cell Li-ion battery pack
Sound Subsystem	Two built-in Acer 3DSonic stereo speakers Intel® High Definition Audio support Built-in microphone SoundBlaster Pro™ and MS Sound compatible
PCCard Support	1 Type II PCCard slot 1 ExpressCard™/54 slot
Pointing Device	Touchpad with Acer Bio-Protection fingerprint reader, featuring Pre-boot Authentication (PBA), computer protection, Acer FingerLaunch, Acer FingerNav
Peripheral Subsystem	4 USB 2.0, 1 IEEE 1394 (4-pin), 1 Fast infrared (FIR) port 1 VGA, 1 S-video/TV-out (NTSC/PAL), Headphones/speaker/line-out jack 1 Microphone jack, 1 Line-in jack 5-in-1 card reader (SD™, MMC, MS, MS PRO, xD) Acer Crystal Eye integrated 310,000 pixel CMOS camera (on selected models only)
Modem	56K ITU V.92 PPT approved, Wake-on-Ring ready
Ethernet	LAN: Gigabit Ethernet supporting ASF (Alert Standard Format) 2.0, Wake-on-LAN ready WLAN: Intel® Wireless WiFi Link 4965AGN (dual-band quad-mode 802.11a/b/g/Draft-N) network connection,

supporting Acer SignalUp™ with InviLink™ Nplify™ wireless technology or Intel® PRO/Wireless 3945ABG (dual-band tri-mode 802.11a/b/g) Wi-Fi CERTIFIED® network connection, supporting Acer SignalUp™ wireless technology
WPAN: Bluetooth® 2.0+EDR (selected models)

Dimensions / Weight 14.17" x 10.51" x 1.09/1.69"
6.36 lbs (with primary battery)

AC Power 100-240V AC AutoSensing Adapter

Environment

Shock 5 G max. pulse / 40 G max. pulse

Operational/Non-Operational

Vibration Non-Operational 5-27HZ, 0.16" p-p, 2g peak, 27-500HZ

Temperature +5°C - +35°C / -20°C - +50°C

Operational/Non-Operational

Humidity 10% - 90% / 10% - 90%

Operational/Non-Operational

Altitude 10,000 ft / 40,000 ft

Operational/Non-Operational

Operating System Windows XP Professional with Service Pack 2
Windows XP Home with Service Pack 2
Windows XP Media Center Edition 2005 with Update Rollup 2
Windows Vista
(varies by model)

[United States](#)

[About Acer](#)

[Contact Support](#)

[Legal](#)

[Privacy](#)

[Register](#)

[Feedback](#)

[Site Map](#)

© 2011 Acer Inc.